


Overview

Product information



15EDGKN-3.81-10020000318

Pluggable terminal blocks, Rated current: 8A.Rated voltage (III/2) : 250V,Cross section: 1.0mm², Pitch: 3.81mm,Color: green, Contact surface : Tin

Product advantages

- ☒ Adapt to multi-type sockets, device design is highly flexible
- ☒ PUSH-IN connection technology, fast wiring
- ☒ Universal installation method, suitable for various situations

Product certification

Technical data

Product drawing

Ambient conditions

Ambient temperature (operation)

-40℃~105℃

Mechanical test

Test Specification

IEC61984/ UL1059

Material data

Flammability rating

UL94V-0

Insulating material group

I

Insulation Materials

PA66

Metal surface terminal point

tin-plated

Contact material

Copper alloy

Environmental Compliance

Compliant with REACH/RoHS

Item properties

Number of positions	6
Pluggable or not	Yes
Connection type	Push-in spring connection

Electrical parameters IEC

Rated surge voltage(II/2)	2.5KV
Rated surge voltage(III/2)	2.5KV
Rated surge voltage(III/3)	2.5KV
Rated voltage (II/2)	250V
Rated voltage (III/2)	160V
Rated Current	8A
Rated voltage (III/3)	160V
Rated Voltage	160V

Electrical parameters UL

Rated current (D)	8A
Rated current (B)	8A
Rated voltage (D)	300V
Rated voltage (B)	300V

Connection capacity

Stripping length	10mm
AWG	28~16AWG
Conductor cross section flexible	0.2~1.0mm ²
Conductor cross section solid	0.2~1.0mm ²

Accessories

Accessory

others	/
Marker strip	/
Plug-in bridge	/
Coding strip	/

Tools

Operating tool	/
Screwdriver	/

Business data

Order number	10020000318
Packing unit	100
Minimum order quantity	
Product weight (without packaging)	3.6