

## Overview

## Product information

**DG333K-3.5-10040001311**

Pluggable terminal blocks, Rated current: 10A, Rated voltage (III/2) 250V, Cross section: 1.0mm<sup>2</sup>, pitch: 3.5mm, connector method: screw connector with wire protection, 蓝色:green, Contact surface: Tin

## Product advantages

- Fixed screw connection technology, safe and reliable
- Different poles can be combined through the side lock

## Product certification



## Technical data

## Product drawing

## 3D model

□

## Connection capacity

Conductor cross section solid	0.5~1.0mm <sup>2</sup>
Conductor cross section flexible	0.5~1.0mm <sup>2</sup>
AWG	28~16AWG
Torque	0.2N.m
Strip length	5mm

## Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	8A

Rated current (D)	8A
-------------------	----

Electrical parameters IEC

Rated current	250V
	10A
Rated current(III/2)	250V
Rated surge voltage(III/2)	2KV

Item properties

Connection method	Screw connection with wire protection
Screwdriver	Slotted screwdriver
screw thread	M2
Pitch	3.5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	Nickel plating
Contact zone metal surface	Nickel plating
Insulation Materials	PBT
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)

-30°C~120°C

#### Accessories

##### Tool

Screwdriver	0.3x2.0mm, Slotted screwdriver
Operating tool	/

##### Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

#### Business data

Order number	10040001311
Packing unit	#NA
Minimum order quantity	30
Products weight (without packaging)	#NA