

## Przegląd

## Informacje o produkcie

**DGK12-002-13030000004**

Building electronic housing ,length :71.6mm,DIN rail housing ,Can be used in distribution box comply with DIN 43880 standard , Upper housing with vent , IP class:IP20.

## Zalety produktu

- Modern design
- flexible PCB connection
- high-efficiency DIN rail connector is optional
- Support Wall-mounted installation and distribution power box installation in accordance with DIN 43880 standards

## Certyfikacja produktu

## Dane techniczne

## Rysunek produktu

## Model 3D

## Dimensions

width	71.6mm
length	89.7mm
Height	60.7mm
Depth from top edge of DIN rail	54.7mm

## PCB data

Number of PCB holders	17 (Upper cover 8+Base 9)
PCB thickness	1.8mm
Installation location	Vertical &horizontal(DIN rail)
PCB type of installation	Latching

**Item properties**

IP class	IP20
Connection levels	1(Both sides)
with ventilation openings	Yes
Maximum connection	44 (pitch : 2.5 mm);24 (pitch : 5 mm),16 (pitch : 7.5 mm)

**Material data**

color	Upper housing: light gray bottom housing: black
Material	PC
Flammability rating	V2

**Environmental data**

Ambient temperature (assembly)	-5°C ~ +100°C
Ambient temperature (operation)	-40°C ~ +110°C
Ambient temperature (storage / transport)	-40°C ~ +70°C

**Akcesoria****Accessories**

--	--

**Dane biznesowe**

numer zamówienia	13030000004
Jednostka opakowania	84
Minimalna ilość zamówienia	84
Waga produktów (bez opakowania)	59.5