

## Przegląd

## Informacje o produkcie

**DG2350-50A(H)-12010000610**

Single-layer PCB barrier terminal blocks, Rated current: 120A. Rated voltage(UL): 600V. Cross section: 2-1/0AWG Pitch: 23.5mm. Color: black, Contact surface: Tin

## Zalety produktu

- Screw connection for worldwide use
- Fence type wiring structure, stable and reliable connection
- High current electrical connections at power end can be met

## Certyfikacja produktu



## Dane techniczne

## Rysunek produktu

## Model 3D

□

## Wiring capacity

torque

5.5N.m

Connectable conductor cross section

2~1/0AWG

## Device properties

number of digits

23.5mm

## Electrical parameters UL

Rated voltage (B)

600V

Rated voltage (C)

600V

Rated voltage (D)

600V

Rated current (B)	120A
Rated current (D)	5A
Rated current (C)	120A

#### Item properties

Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	Phillips screwdriver
screw thread	M8
Number of potentials	4
Pluggable or not	no
Number of rows	1

#### Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PBT
Insulating material group	IIIa
Flammability rating	UL94V-0

#### Mechanical tests

Test Specification	UL1059
--------------------	--------

#### Environmental data

Ambient temperature (operation)	-40°C~125°C
---------------------------------	-------------

Akcesoria

Dane biznesowe

numer zamówienia	12010000610
Jednostka opakowania	20
Minimalna ilość zamówienia	
Waga produktów (bez opakowania)	195.66