

Przegląd

Informacje o produkcie

**D3A-SF-1L-PG13.5-21010000416**

3A Lower base, single buckle, no back cover, PG13.5 Thread hole

Zalety produktu

- Metal or high-strength plastic material, resistant to high-strength mechanical shock;
- Various installation methods and outlet directions to meet on-site wiring requirements;
- Snap-in combination structure, dustproof, waterproof, easy operation;

Certyfikacja produktu

Dane techniczne

Rysunek produktu

Model 3D

□

Marking

| | |
|----------------|--------------------|
| classification | Upper Housing/base |
| Series | A |
| Type | Hole mounting base |
| Specification | Low structure |

versions

| | |
|----------------------|-------------|
| Dimension | 3A |
| locking Category | Single lock |
| Thread specification | 1x PG13.5 |

Material characteristics

| | |
|-------------------------------|---------------------|
| Flammability rating | V-0 |
| RoHS | conform |
| Material (upper housing/base) | Die-cast zinc alloy |
| Material(upper housing/base) | spray |
| Color (upper housing/base) | Grey (RAL 7037) |
| Material (seal) | NBR |
| Material (lock catch) | Stainless steel |

Technical specification

| | |
|-----------------------|--------------|
| Limiting temperatures | -40°C~+125°C |
| IP class | IP65 |

Aksesoria

Dane biznesowe

| | |
|---------------------------------|-------------|
| numer zamówienia | 21010000416 |
| Jednostka opakowania | 100 |
| Minimalna ilość zamówienia | 1 |
| Waga produktów (bez opakowania) | 55 |