

## Przegląd

### Informacje o produkcie



## 16A-GM-0.75-92116900052

16A silver gold male pins, Adapter wire specification 0.75mm<sup>2</sup>

### Zalety produktu

- High-precision turning process, stable and reliable products;
- Gold-plated and silver-plated are available, suitable for different environmental requirements;
- Comprehensive products, resistant to temperature changes, shocks and harsh environments.

### Certyfikacja produktu

## Dane techniczne

### Rysunek produktu

### Model 3D

□

### Marking

classification	Contact
Series	16A
Contact type	Crimping contact

### versions

Female/Male	Male
manufacturing technique	Turning

### Material characteristics

RoHS	Comply with RoHS exemptions
Plating material	Gold plate
Material	Copper alloy

## Standards

Connection meets standards

EN 60664-1 IEC 61984

## Technical specification

Conductor cross sections (mm <sup>2</sup> )	0.75mm <sup>2</sup>
Conductor cross sections(AWG)	18AWG
Working current	≤16A
Contact resistance	≤1mΩ
Plating Thickness	≥3μ"
Temperature range	-40°C~+125°C
Strip length	7.5mm
working life-mating cycles	≥500

## Akcesoria

## Dane biznesowe

numer zamówienia	92116900052
Jednostka opakowania	100
Minimalna ilość zamówienia	100
Waga produktów (bez opakowania)	1.57