

Przegląd

Informacje o produkcie



16A-GM-4.0-92116900056

16A silver gold male pins, Adapter wire specification 4.0mm²

Zalety produktu

- High-precision turning process, stable and reliable products;
- Gold-plated and silver-plated are available, suitable for different environmental requirements;
- Comprehensive products, resistant to temperature changes, shocks and harsh environments.

Certyfikacja produktu

Dane techniczne

Rysunek produktu

Model 3D

□

Marking

classification	Contact
Series	16A
Contact type	Crimping contact

versions

Female/Male	Male
manufacturing technique	Turning

Material characteristics

RoHS	Comply with RoHS exemptions
Plating material	Gold plate
Material	Copper alloy

Standards

Connection meets standards

EN 60664-1 IEC 61984

Technical specification

Conductor cross sections (mm ²)	4.0mm ²
Conductor cross sections(AWG)	12AWG
Working current	≤16A
Contact resistance	≤1mΩ
Plating Thickness	≥3μ"
Temperature range	-40°C~+125°C
Strip length	7.5mm
working life-mating cycles	≥500

Akcesoria

Dane biznesowe

numer zamówienia	92116900056
Jednostka opakowania	100
Minimalna ilość zamówienia	100
Waga produktów (bez opakowania)	1.57