


## Aperçu

## informations sur le produit

**TSB2.5-10070000028**

Transformer terminal blocks, Rated current: 24A. Rated voltage (III/2) : 250V, Color: Orange, Contact surface : Tin

## Les avantages des produits

- Screw connection technology, safe and reliable
- Rail installation method, suitable for transformer wiring

## Les certificats des produits



## Caractéristiques techniques

## Dessin de produit

## Modèle 3D

□

## Connection capacity

Conductor cross section solid	0.5~2.5mm <sup>2</sup>
Conductor cross section flexible	0.5~2.5mm <sup>2</sup>
AWG	20~12AWG
Torque	0.8N.m
Strip length	9mm

## Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V

Rated current (B)	20A
Rated current (D)	5A
Rated current (C)	20A

#### Electrical parameters IEC

Rated current	250V
	24A
Rated current(III/2)	250V
Rated surge voltage(III/2)	2KV

#### Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	slotted-Phillips screwdriver
screw thread	M3.5
Pitch	9.5mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

#### Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

#### Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

#### Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

#### Accessoires

##### Accessories

Coding strip	TZB4
Bridge	/
Marking strip	/
Others	/

##### Tool

Operating tool	/
Screwdriver	/

#### Caractéristiques commerciales

Numéro de la commande	10070000028
Unité d'emballage	450
Quantité minimale de commande	30
Le poids de produit (sans emballage)	8.72