

## Overview

### Product information



## PCSH-M23R-12P-MM-SL7001-00A(H)-20050000012

Motor connector, M23 × 1-pin on-site assembly plug, straight head, shielded.  
Rated voltage: 630V, rated current: 28 A, connection method: crimping type,  
contact type: pin type

### Product advantages

- Cross manufacturer compatibility and global universality.
- Multiple combination methods to meet various installation environments.
- 360 ° full shielding, suitable for complex electromagnetic interference and other environments.
- Optimize the structure. Improve the locking of the end of the line to reduce potential faults; Innovate anti backflow needles to prevent internal structural looseness; Secondary fastening improves product reliability.
- It has seismic resistance and can ensure high reliability of the product even in harsh environments.
- Easy to install, even non professionals can quickly assemble and replace defective parts.
- The test report is complete.

### Product certification



## Technical data

### Product drawing

### 3D model



### Overview

shield

Yes

### Environment condition

Ambient temperature (operation)

-40°C ~ +125°C

### Technical parameter

Withstand voltage

2000V AC

### General parameters

Rated current	8A
	160V
Number of potentials	12
Insulation resistance	≥ 100 MΩ

#### Technical specification

IP class	IP67
----------	------

#### Accessories

#### Business data

Order number	20050000012
Packing unit	10
Minimum order quantity	/
Products weight (without packaging)	/