


## Aperçu

## informations sur le produit

**DC2.5-12A(H)-11020000058**

Screw type Din-Rail TB, connector method: Screw/plug-in connector, Rated voltage: 800 V, Rated current: 24 A, Number of connectors: 2, Number of potentials: 1, Cross section: 0.2 mm<sup>2</sup> - 4 mm<sup>2</sup>, AWG: 28 - 12, Width: 5.1 mm, Color: gray, Mounting type: NS 35/7.5, NS 35/15

## Les avantages des produits

- Steel screw connection technology, reliable connection;
- Equipped with dual-channel bridge wells, circuit connection testing is more flexible;
- Unique plug-in bridge, high circuit connection efficiency;
- The box has a baffle to prevent mis-insertion;
- Can be matched with marker strips to avoid incorrect insertion of wires.

## Les certificats des produits



## Caractéristiques techniques

## Dessin de produit

## Modèle 3D

□

## Wiring data

Screw type	Cross & Slotted screw
Conductor cross section flexible (ferrule with plastic sleeve)	0.5-1.5mm <sup>2</sup>
Strip length	8~9mm
Conductor cross section solid	0.2~4mm <sup>2</sup>
Conductor cross section flexible	0.2~2.5mm <sup>2</sup>
Conductor cross section solid AWG	28~12
screw thread	M2.5

Tightening torque	0.4N.m
-------------------	--------

#### Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

#### UL Electrical parameters

Rated current	25A
---------------	-----

#### IEC Electrical parameters

Rated voltage (III / 3)	800V
Rated current (III / 3)	24A
Rated surge voltage	8KV

#### Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

#### Dimension

NS 35/7,5 Height	41.5mm
End plate width	1.5mm
NS 35/15 Height	49mm
length	44.5mm
width	5.1mm
Height	40mm

#### Overview

Connection method	screw connection
Number of rows	1
number of connections	2
Open-end side panels	Yes

Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

## Accessoires

### Marker

Top marker	/
Side marker	ZB5 / WB5
Marker support	/

### Accessories

Slotted screwdriver size (Blade thickness x Width)	0.6x3.5
Bridge	DFA2.5
End cover	D-DC2.5
Partition plate	/

### Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

## Caractéristiques commerciales

Numéro de la commande	11020000058
Unité d'emballage	100
Quantité minimale de commande	100
Le poids de produit (sans emballage)	4.765