

Overview

Product information



ESS-200A-50-B-OR-90-20160000005

Energy Storage Connector, Product range: ESS socket, Color: orange, Wire cross section: 50 mm², Rated voltage: 1500V, Rated current: 200 A, Connection method: Busbar, Contact type: Pin

Product advantages

- Exclusive patents
- IP67 protection
- With safety locking latch
- The plug can rotate 360° after assembled
- The socket is with hand-proof protection
- With color-coded and mechanism-coded design avoiding misplug

Product certification



Technical data

Product drawing

3D model

□

Wiring data

Wiring mode

Busbar

Environmental conditions

Operating ambient temperature (including temperature rise)

-40°C-125°C

Environment condition

Protection grade (pair plug)

IP67

Ambient temperature (storage/transportation)

-40°C ~ +80°C

Altitude

2000m

Mechanical properties

Plugging times	100
Pullout force	>10N

Mechanical properties

Insertion force	< 100N
-----------------	--------

Standards and specifications

Standard/Specification	UL4128
------------------------	--------

Material data

Insulating material	Nylon
Halogen-free	Compliance with standards
Environmental protection matters	REACH/RoHS compliant
Sealing ring material	Silicone
Contact material	Copper alloy
Shell color	Orange
Flammability rating	UL94V-0

Electrical parameters

Pollution level	3
Rated current	UL DC1500V
	200A
Insulation resistance	>5000MΩ
Contact resistance	≤0.5mΩ

Accessories

Business data

Order number	2016000005
Packing unit	50
Minimum order quantity	50
Products weight (without packaging)	46