


## Overview

## Product information

**DGR200-U-12010001164**

Transfer barrier terminal blocks, Rated current:200A. Rated voltage (UL) :600V, Cross section:6~4/0AWG, pitch:35mm, Color:black, Contact surface: Tin

## Product advantages

- Screw connection for worldwide use
- Fence type wiring structure, stable and reliable connection
- Provide the cabinet and panel electrical transfer connections

## Product certification



## Technical data

## Product drawing

## 3D model

□

## Connection capacity

AWG	6~4/0AWG
-----	----------

## Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V
Rated current (B)	200A
Rated current (D)	5A
Rated current (C)	200A

## Item properties

Type of installation	panel
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	Phillips screwdriver
screw thread	M10
Pitch	35mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

#### Material data

Environmental items	Compliant with REACH/RoHS
Contact material	steel
Contact point metal surface	Galvanized
Insulation Materials	PC
Insulating material group	IIIa
Flammability rating	UL94V-0

#### Mechanical tests

Test Specification	UL1059
--------------------	--------

#### Environmental data

Ambient temperature (operation)	-40°C~105°C (depending on derating curve)
---------------------------------	---

#### Accessories

#### Business data

Order number	12010001164
--------------	-------------

Packing unit	12
Minimum order quantity	
Products weight (without packaging)	312.2