


Overview

Product information



STB4-TW-11100000020

Pull back rail terminal, wiring method: pull back spring connection, rated voltage: 800V, rated current: 24A, connection quantity: 3, number of digits: 1, wiring capacity: 0.14mm² -6mm², AWG: 28-12, width: 6.15mm, color: gray, installation method: NS35/7.5, NS35/15

Product advantages

- The proven pullback connection technology has excellent seismic performance
- Can be connected to rated wires with or without cold heads
- Dual channel bridging well, with 2-20 bridge connectors for flexible separation
- Clear front identification, easily recognizable marking area

Product certification

Technical data

Product drawing

3D model

□

Overview

Connection method	spring-cage connection
Number of rows	1
number of connections	3
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0
Insulating material group	I
standard test	IEC60947-7-1

Dimension

width	5.2mm
End plate width	1.5mm
Height	30.25mm
NS 35/7,5 Height	37.75mm
NS 35/15 Height	45.25mm
length	72.5mm

Wiring data

Strip length	9~10mm
Conductor cross section solid AWG	28~10
Conductor cross section solid	0.08-4mm ²
Conductor cross section flexible	0.08-4mm ²
Conductor cross section flexible (ferrule without plastic sleeve)	0.08-4mm ²
Conductor cross section flexible (ferrule with plastic sleeve)	0.08-4mm ²

IEC Electrical parameters

Rated current (III / 3)	32A
Rated surge voltage	8KV

UL Electrical parameters

Rated voltage	600V
Rated current	30A

UL Electrical parameters

Rated voltage (Use Group B)	600V
-----------------------------	------

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

Ambient temperature (storage / transport)	-25°C~60°C
---	------------

Mechanical performance test

Mechanical strength	Passed the test
Fixing support	Passed the test
Rotational Pull Test	Passed the test

Electrical performance test

Voltage drop	≤3.2mV
Temperature rise test	≤45 K

Safety test

Anti-finger touch	Passed the test
-------------------	-----------------

Environmental protection

RoHS	No excessive harmful substances
REACH SVHC	Lead 7439-92-1

Accessories

Marker

Top marker bar	ZS6/ZB6
Side marking strip	ZSF6/ZT6

Accessories

A screwdriver	0.6x3.5
Bridge components	DFBSXXX-6.2(XXX:2,3,4,5,6,7,8,9,10,20)
End plate	D-STB4-TW
Grouping partition	ATP-DS / ATP-PC N

Installation

Terminal fixing components	E-PC 1100A / E-WS N
----------------------------	---------------------

Terminal strip marking bracket	DLM2 / KLM3-20x8 / KLM3-44x8
DIN rail	NS35/7.5-1000-00A(H)
Guide rail protection cover	AP3-COVER / AP3-T / AP3-T-KS

Business data

Order number	11100000020
Packing unit	40
Minimum order quantity	40
Products weight (without packaging)	12.13