

## Overview

## Product information

**Push-in connection relay Socket-DPRC-05A-F3-00A(H)-30020000133**

DPRC Relay Socket, used for 1 PDT relay, push-in connection

## Product advantages

- Push-in relay socket
- Safe isolation between coils and contacts
- 12A maximum switching current

## Product certification



## Technical data

## Product drawing

## 3D model

□

## Dimension

width	16mm
length	99.6mm
Depth including bracket	42mm

## Environmental data

Ambient temperature (operation)	-45°C ~ +85°C
Ambient temperature (storage / transport)	-45°C ~ +85°C

## Technical data

Rated voltage UN	300V
------------------	------

Rated current IN	12A
Installation location	Arbitrary
Assembly instructions	DIN35 rail

#### Connection data 1

Connection name	enter
Connection method	PUSH-IN connection
Stripping length	10-12mm
Cross section of flexible conductor	0.25-2.5mm <sup>2</sup>
Connectable guide cross section AWG	22-14AWG

#### Connection data 2

Connection name	Output
Stripping length	10-12mm
Cross section of flexible conductor	0.25-2.5mm <sup>2</sup>
Connectable guide cross section AWG	22-14AWG
Connection method	PUSH-IN connection

#### Accessories

##### Accessory

Bridge	DFB2-13-12-00A(H) DFB2-13-13-00A(H)
--------	-------------------------------------

#### Business data

Order number	30020000133
Packing unit	10 SKT
Minimum order quantity	10 SKT

Products weight (without  
packaging)

35g