

## Overview

### Product information



**SD-M8A-03P-MM-SH7002-20020000416**

Sensor/Actuator Female socket, M8, Coding A, Front panel installation/M8\*0.5  
Thread mounted, Soldering cup

### Product advantages

- Sealing optimization, protection level up to IP67
- Meet the harsh environment
- Miniature connector, Space saving
- Suitable for various occasions connection technology
- Compatible with the international and domestic same series products

### Product certification



**RoHS**

**REACH**



## Technical data

### Product drawing

### 3D model

□

### Environmental conditions

Ambient temperature	-40°C...105°C
IP class	IP67

### General parameters

Rated current	3A
	60V
Number of potentials	3
Insulation resistance	≥ 100 MΩ
Error-proof coding	A-Code

Overvoltage level	II
Pollution level	3
Connection method	Soldering
Insertion and pullout cycle	≥ 100
Torque	0.3 Nm ... 0.4 Nm
Type of installation	Installation in front of the board

#### Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PA
Coil material	Copper alloy, nickel plated
Sealing material	Silicon

#### Standards and specifications

Standards/specifications	IEC 61076-2-104
--------------------------	-----------------

#### Accessories

#### Business data

Order number	20020000416
Packing unit	/
Minimum order quantity	100
Products weight (without packaging)	/