Overview

Product information



DCKKB2.5-11020000073

Screw type Din-Rail TB， connector method: Screw/plug-in connector， Rated voltage: 500 V，Rated current: 24 A， Number of connectors: 4， Number of potentials: 1， Cross section: 0.2 mm² - 4 mm²， AWG: 28 - 12， Width: 5.1 mm， Color: gray， Mounting type: NS 35/7.5， NS 35/15

Product advantages

☑Steel screw connection technology, reliable connection；
☑Equipped with dual-channel bridge wells, circuit connection testing is more flexible；
☑Unique plug-in bridge, high circuit connection efficiency；
☑The box has a baffle to prevent mis-insertion；
☑Can be matched with marker strips to avoid incorrect insertion of wires。

Product certification

Technical data

Product drawing

3D model

Overview

Number of rows	2
number of connections	4
Open-end side panels	Yes
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0
Insulating material group	I

standard test	IEC60947-7-1
Connection method	screw connection

Dimension

width	5.1mm
End plate width	1.5mm
Height	61.8mm
NS 35/7,5 Height	63mm
NS 35/15 Height	70.5mm
length	76mm

Wiring data

Strip length	8~9mm
Conductor cross section solid AWG	28~12
Conductor cross section solid	0.2~4mm²
Conductor cross section flexible	0.2~2.5mm²
Conductor cross section flexible (ferrule without plastic sleeve)	0.2-2.5mm²
Conductor cross section flexible (ferrule with plastic sleeve)	0.5-1.5mm²
2 flexible conductors with a TWIN ferrule	0.5-1mm²
Screw type	Slotted screw
screw thread	M2.5
Tightening torque	0.4N.m

IEC Electrical parameters

Rated voltage (III / 3)	500V
Rated current (III / 3)	24A
Rated surge voltage	6KV

UL Electrical parameters	
Rated voltage	300V
Rated current	20A
Environmental conditions	
Ambient temperature (operation)	-40 °C ~ 105 °C（depending on derating curve）
Relative humidity (storage/transport)	25%~75%
Ambient temperature (storage / transport)	-25℃~60℃
Mechanical performance test	
Mechanical strength	Passed the test
Fixing support	Passed the test
Rotational Pull Test	Passed the test
Electrical performance test	
Voltage drop	≤3.2mV
Temperature rise test	≤45 K
Safety test	
Anti-finger touch	Passed the test
Environmental protection	
RoHS	No excessive harmful substances
REACh SVHC	Lead 7439-92-1

Accessories

Marker	
Top marker	/
Side marker	ZB5 / WB5
Marker support	/

Accessories

Slotted screwdriver size (Blade thickness x Width)	0.6×3.5
Bridge	DFA2.5
End cover	D-DCKKB2.5
Partition plate	/

Installation

End clamp	E-WS N / E-PC-1100A
Terminal strip marker support	KLM3-20x8 / KLM3-44x8 / DLM2 / DBE-1 / DBE-2
DIN rail	NS35/7.5 & NS35/15

Marking & Installation

Marking strip	ZB5
Marker cards	DBE-1

Accessories

End cover	D-DCKKB2.5
Bridge	DFA2.5
End clamp	E-WS
DIN rail	NS35/7.5-1000-00A(H)

Business data

Order number	11020000073
Packing unit	50
Minimum order quantity	50
Products weight (without packaging)	11.64