


Visión general

Información del Producto



8EDGRCB-7.5-10030002825

Pluggable terminal blocks, Rated current: 20A. Rated voltage (III/3) : 400V, pitch: 7.5mm, Color: gray, Contact surface : Tin

Ventajas del producto

- ☒ Universal installation method to ensure a high degree of flexibility in device design
- ☒ The plug direction is parallel to the PCB

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D

□

Processing notes

Process

Wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	15A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	400V
Rated voltage(III/3)	400V

Rated current	20A
Rated surge voltage(III/3)	4KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Pitch	7.5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

Accesorios

Tool

Screwdriver	/
-------------	---

Operating tool	/
----------------	---

Accessories

Coding strip	DG015
Bridge	/
Marking strip	/
Others	/

Datos empresariales

Número de pedido	10030002825
Unidad de embalaje	200
Cantidad mínima de pedido	
Peso del producto (sin embalaje)	0.9