


Visión general

Información del Producto



DG264-15.0-10060001640

PCB spring terminal blocks, Rated current: 76A. Rated voltage
(III/2) : 1000V, pitch: 15.0mm, Color: gray, Contact surface : Tin

Ventajas del producto

- ☒ Universal installation method, suitable for various situations
- ☒ 45° connection can realize multi-row layout on PCB
- ☒ Different poles can be combined through the side lock

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D

□

Processing notes

Process

Wave soldering/manual soldering

Connection capacity

Conductor cross section solid

0.2~16mm²

Conductor cross section flexible

0.2~16mm²

AWG

24~4AWG

Strip length

12mm

Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (C)

300V

Rated voltage (D)	300V
Rated current (B)	66A
Rated current (D)	10A
Rated current (C)	66A

Electrical parameters IEC

Rated voltage	1000V
Rated voltage(III/3)	630V
Rated current	76A
Rated voltage(III/2)	1000V
Rated voltage(II/2)	1000V
Rated surge voltage(III/3)	8KV
Rated surge voltage(III/2)	8KV
Rated surge voltage(II/2)	8KV

Item properties

Connection direction	45°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Connection method	spring-cage connection
Pitch	15mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
---------------------	---------------------------

Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL 1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

Accesorios

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Datos empresariales

Número de pedido	10060001640
Unidad de embalaje	95
Cantidad mínima de pedido	
Peso del producto (sin embalaje)	18.355

