

Visión general

Información del Producto

**SD-M8B-05P-MM-SF7003-20020000476**

Sensor/Actuator Female socket,M8,Coding B,Rear panel installation/M8*1.0
Thread mounted,Soldering cup

Ventajas del producto

- ✓ Sealing optimization, protection level up to IP67
- ✓ Meet the harsh environment
- ✓ Miniature connector,Space saving
- ✓ Suitable for various occasions connection technology
- ✓ Compatible with the international and domestic same series products

Certificación del producto

**RoHS****REACH**

Datos técnicos

Dibujo del producto

Modelo 3D

□

Environmental conditions

Ambient temperature

-40°C...105°C

IP class

IP67

General parameters

Rated current

3A

30V

Number of potentials

5

Insulation resistance

≥ 100 MΩ

Error-proof coding

B-Code

Overvoltage level	II
Pollution level	3
Connection method	Soldering
Insertion and pullout cycle	≥ 100
Torque	0.3 Nm ... 0.4 Nm
Type of installation	Rear board installation

Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Material contact surface	Au
Contact carrier material	PA
Coil material	Copper alloy, nickel plated
Sealing material	Silicon

Standards and specifications

Standards/specifications	IEC 61076-2-104
--------------------------	-----------------

Accesorios

Datos empresariales

Número de pedido	20020000476
Unidad de embalaje	/
Cantidad mínima de pedido	100
Peso del producto (sin embalaje)	/