


Visión general

Información del Producto



2EDGAM-7.62-10020001936

Pluggable terminal blocks, Rated current: 20A. Rated voltage (III/2) : 400V, pitch: 7.62mm, Color: green, Contact surface : Tin

Ventajas del producto

- ☒ PCB welding, plug direction is parallel to the PCB
- ☒ Multiple contacts to provide touch protection for connection

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D

□

Processing notes

Process

Wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	15A
Rated current (D)	15A

Electrical parameters IEC

Rated voltage	400V
Rated voltage(III/3)	400V

Rated current	20A
Rated voltage(III/2)	400V
Rated voltage(II/2)	1000V
Rated surge voltage(III/3)	4KV
Rated surge voltage(III/2)	4KV
Rated surge voltage(II/2)	4KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Pitch	7.62mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

Accesorios

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Tool

Operating tool	/
Screwdriver	/

Datos empresariales

Número de pedido	10020001936
Unidad de embalaje	600
Cantidad mínima de pedido	
Peso del producto (sin embalaje)	2.203