


Visión general

Información del Producto



15EDGRM-THR-3.81-10030004052

Pluggable terminal blocks, Rated current: 8A. Rated voltage
(II / 2) : 250V, pitch: 3.81mm, Color: black, Contact surface : Tin

Ventajas del producto

- ☒ Suitable for SMT welding process
- ☒ The plug direction is parallel to the PCB, Can meet the needs of different connectors

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D

□

Processing notes

Process

Reflow soldering/wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)

300V

Rated current (B)

8A

Electrical parameters IEC

Rated voltage

250V

Rated current

8A

Rated voltage(II/2)

250V

Rated surge voltage(II/2)

2.5KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Pitch	3.81mm
Number of potentials	4
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact zone metal surface	tin-plated
Insulation Materials	High temperature resistant materials
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL1059
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40°C~130°C
---------------------------------	-------------

Accesorios

Tool

Screwdriver	/
Operating tool	/

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Datos empresariales

Número de pedido	10030004052
Unidad de embalaje	350
Cantidad mínima de pedido	
Peso del producto (sin embalaje)	1.805