

Visión general

Información del Producto



DG220B-2.1-10060002741

PCB spring terminal blocks, Rated current: 6A. Rated voltage
(III/2) : 320V, pitch: 2.1mm, Color: gray, Contact surface : Tin

Ventajas del producto

- ☒ PUSH-IN connection technology, fast wiring
- ☒ Suitable for single wire
- ☒ Wire Connector for Mini Junction Box

Certificación del producto



Datos técnicos

Dibujo del producto

Modelo 3D

□

Connection capacity

Conductor cross section solid

0.5~1.0mm²

Strip length

6mm

Electrical parameters UL

Rated voltage (B)

150V

Rated voltage (D)

150V

Rated current (B)

7A

Rated current (D)

7A

Electrical parameters IEC

Rated voltage	320V
Rated voltage(III/3)	250V
Rated current	6A
Rated voltage(III/2)	320V
Rated voltage(II/2)	630V
Rated surge voltage(III/3)	4KV
Rated surge voltage(III/2)	4KV
Rated surge voltage(II/2)	4KV

Item properties

Connection direction	0°
Connection method	Push-in spring connection
Pitch	2.1mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)

-40°C~105°C

Accesorios

Accessories

Coding strip

/

Bridge

/

Marking strip

/

Others

DG220J

Tool

Operating tool

/

Screwdriver

/

Datos empresariales

Número de pedido

10060002741

Unidad de embalaje

1250

Cantidad mínima de pedido

Peso del producto (sin
embalaje)

0.413