


## Visión general

### Información del Producto



## 2EDGKDRN-5.08-10020002803

Pluggable terminal blocks, Rated current: 20A. Rated voltage  
(III/2) : 320V, pitch: 5.08mm, Color: green, Contact surface : Tin

### Ventajas del producto

- ☒ Adapt to multi-type sockets, device design is highly flexible
- ☒ Keying requirements can be met
- ☒ Universal installation method, suitable for various situations

### Certificación del producto



## Datos técnicos

### Dibujo del producto

### Modelo 3D

□

### Connection capacity

|                                  |                        |
|----------------------------------|------------------------|
| Conductor cross section solid    | 0.2~2.5mm <sup>2</sup> |
| Conductor cross section flexible | 0.2~2.5mm <sup>2</sup> |
| AWG                              | 26~12AWG               |
| Strip length                     | 9mm                    |

### Electrical parameters UL

|                   |      |
|-------------------|------|
| Rated voltage (B) | 300V |
| Rated current (B) | 10A  |

### Electrical parameters IEC

|               |      |
|---------------|------|
| Rated voltage | 250V |
|---------------|------|

|                                     |       |
|-------------------------------------|-------|
| Rated current                       | 12A   |
| Rated voltage(III/2)                | 250V  |
| Rated power frequency voltage(1min) | 2.5KV |

Item properties

|                      |                           |
|----------------------|---------------------------|
| Connection direction | 0°                        |
| Connection method    | Push-in spring connection |
| Pitch                | 5.08mm                    |
| Number of potentials | 4                         |
| Pluggable or not     | Yes                       |
| Number of rows       | 1                         |

Material data

|                             |                           |
|-----------------------------|---------------------------|
| Environmental items         | Compliant with REACH/RoHS |
| Contact material            | copper                    |
| Contact point metal surface | tin-plated                |
| Insulation Materials        | PA66                      |
| Insulating material group   | I                         |
| Flammability rating         | UL94V-0                   |

Mechanical tests

|                    |                  |
|--------------------|------------------|
| Test Specification | IEC61984/ UL1059 |
|--------------------|------------------|

Environmental data

|                                 |           |
|---------------------------------|-----------|
| Ambient temperature (operation) | -40℃~105℃ |
|---------------------------------|-----------|

Accesorios

Accessories

|               |   |
|---------------|---|
| Coding strip  | / |
| Bridge        | / |
| Marking strip | / |
| Others        | / |

Tool

|                |   |
|----------------|---|
| Operating tool | / |
| Screwdriver    | / |

Datos empresariales

|                                  |             |
|----------------------------------|-------------|
| Número de pedido                 | 10020002803 |
| Unidad de embalaje               | 385         |
| Cantidad mínima de pedido        |             |
| Peso del producto (sin embalaje) | 6.8         |