

총람

제품 장점



DG332JR-5.0-10030003050

Needle connector, Rated current: 12A, Rated voltage (III/2) 250V, pitch: 5.0mm, Color: black, Contact surface: Tin

제품 장점

- ☒ Adapt to multi-type plugs, device design is highly flexible
- ☒ Universal installation method

제품 인증



기술 데이터

제품 도면

3D

□

Processing notes

Process

Wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)

300V

Rated current (B)

10A

Electrical parameters IEC

Rated voltage

250V

Rated current

12A

Rated voltage(III/2)

250V

Rated surge voltage(III/2)

2KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Pitch	5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

악세서리

Tool

Screwdriver	/
Operating tool	/

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

비즈니스 데이터

발주 번호	10030003050
포장 단위	2000
MOQ	30
제품 무게 (포장 제외)	0.55