

C


PMSH-M12B-05P-FF-SR8D01-2003000102e

Snsor / Aktua ur / D bln, PUD, bl t k, L42519, Fnm ln Qlag, csglnd, M12, Dr disg
B, Shindnd, T/immisg bln Qsd, D bln D bln Qhsguh: 1m, L4 Dn / ufit ur s

C

- ☒ Sn llsig pumiz ur s, Q/r unt ur s Qhvn l Qp Q IP68
- ☒ Mnnu Qhnd / oh Qsvi / r smnsu
- ☒ Saiu bln Q / Q / ir ao Q t t oir so Q r ssnt ur s Qnt hsr lrgy
- ☒ Dr mp ubln Q h Qhnd Qsun / s ur s ICsd Qr mnoit Q mn Qn / ino Q / r dat uo

C






C

C

3G

□

Esvi / r smnsu l Q r sdi ur so

cmbinsu Qhmpn / u / n

-25°C...85°C

IP Q l oo

IP68

Onsn / l Q / mnun / o

R und Q a / nsu

Vc

60U

Nambn / Q f Q r unsi lo

5

Isoal ur s Qnoiou st n

≥ 1000 MΩ

E / r / - p / r r f Q r disg

B-Dr dn

q vn/vr lu gn	II
Pr llaür s	3
lson/ür sCsd	≥100
Tr /Zan	0.0m

M un/i l

Fl mm biliyC üsgQsQsnQihC.4eV	U0
Drsu tu	Daxs
M un/i lCrsu tu	ca
Drsu tuC //in/	Pc
Fi7a/nCrdy	TPL
Dr il	xist Cllr y,Git knl
Sn lisg	Silit r s

Su sd /doCsd

Su sd /do	IED1096-2-101
-----------	---------------

D bln

D bln	PUD
D bln(bb/nvi ürs)	PUD
L4CWM	L42519
D/r oo	0.3Vmm²
cWOQigs l	22cWO
Wi/nQat a/nSigs l	19A.16mm²
Dr /nQi mnun/Qist ladisg	1.30±0.05mm
Wi/nCrlr /	1C/rws20WhiunCBlanCBl tkC/ yCsiuisg
Thit ksnoo,	0.6mm
D blnCau/nQi mnun/C	5.9±0.2mm

Outer sheath, material	PU
Conductor insulation material	PE
Conductor material	Tinned copper
Conductor resistance	Maximum 59.4Ω/km (at 20 °C)
Nominal cable voltage	300V
Cable test voltage	2000V
Flame retardant	Comply with UL 758/1581 FT2 standard
Halogen free	No

Dimension

Cable length	1m
--------------	----

Accessories

Sealing cap	CAP-M12-MP-8001
-------------	-----------------

!

	20030001030
	/
MOQ	100
()	/