

총람

제품 장점



PASH-M8B-05P-FF-SL7001-20020000009

Field mounted, Shielded, Female, Straight, M8, Coding B, Soldering connector, Cable External cable diameter 4.0~6.0 mm

제품 장점

- ☑ Sealing optimization, protection level up to IP67
- ☑ Meet the harsh environment
- ☑ Miniature connector, Space saving
- ☑ Suitable for various occasions connection technology
- ☑ Compatible with the international and domestic same series products

제품 인증



RoHS

REACH



기술 데이터

제품 도면

3D

□

Environmental conditions

Ambient temperature

-40℃...85℃

IP class

IP67

General parameters

Rated current

3A

30V

Number of potentials

5

Insulation resistance

≥ 100 MΩ

Error-proof coding

B-Code

Overvoltage level	II
Connection method	Soldering
Insertion and pullout cycle	≥ 100
Torque	0.3 Nm ... 0.4 Nm

Material

Flammability rating ,in line with UL94	V0
Contact material	CuZn
Contact carrier material	PA
Coil material	Copper alloy, nickel plated
Sealing material	Silicon

Standards and specifications

Standards/specifications	IEC 61076-2-104
--------------------------	-----------------

Dimension

Assembled cable outer diameter	4.0-6.0mm
Assembled conductor cross section	0.25~0.34 mm²
	24~22 AWG

악세사리

비즈니스 데이터

발주 번호	20020000009
포장 단위	/
MOQ	100
제품 무게 (포장 제외)	/