DEGSON

## Overview

### Product information

# PV-ST-MM-PSW-20P-00A(H)-29030000019

Used in communication signal connection; Rated current 1.5A; Rated voltage 30V; Resistant voltage 500V AC; Wiring mode welding; Protection Class IP67 (Plug)

### Product advantages

☑ IP66 dustproof and waterproof
☑ TUV certification

### Product certification

RoHS REACH

## Technical data

### Product drawing

### 3D model

### Environmental conditions

| | |
|---|---|
| Ambient temperature (operation) | -40 °C ~ 85 °C |

### Environmental protection

| | |
|---|---|
| RoHS | No excessive harmful substances |

### Environment condition

| | |
|---|---|
| Protection grade (pair plug) | IP67 |

### Mechanical properties

| | |
|---|---|
| Plugging times | 100 |

### Technical parameter

| | |
|---|---|
| Withstand voltage | 500V AC |

| | |
|---|---|
| insulation resistance | ≥100MΩ |

Versions

| | |
|---|---|
| Female/Male | Female |

General parameters

| | |
|---|---|
| Rated current | 1.5A |
| | 30V |

Accessories

Business data

| | |
|---|---|
| Order number | 29030000019 |
| Packing unit | 20 |
| Minimum order quantity | / |
| Products weight (without packaging) | 318 |