


Überblick

Informationen zum Produkt



DMK-003-FC-21020000140

Heavy-duty insert, Number of contacts: 3, Dimension: 1 module Spaces, Rated voltage : 500V, Rated current: 40A, Female insert, Crimping connector

Produktvorteile

- ☑ Crimping connection technology, applicable to a wide range of wire specifications ;
- ☑ Modular products, easy to assemble and maintain .

Zertifizierung von Produkten



Technische Daten

Produktzeichnung

3D-Modell

□

Marking

classification	Insert
Series	DM

versions

Connection method	Crimping connection
Female/Male	Female
Dimension	1 module
Number of positions	3
PE Contacts	No

Material characteristics

Material (insert)	Polycarbonate (PC)
Materia (Contact)	Copper alloy
Surface (Contact)	Silver plated/gold plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	40A
	500V
Rated pulse voltage	8KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤0.3mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Conductor cross sections (mm²)	1.5-10mm²
Conductor cross sections(AWG)	16-8AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

Zubehör

Accessories

Crimping tool Removal tool	/
----------------------------	---

Die Geschäftsdaten

Nummer der Bestellung	21020000140
Verpackung Einheit	
Minimale Bestellmenge	5
Produktgewicht (ohne Verpackung)	13.3