


Überblick

Informationen zum Produkt



DMD-012-FC-21020000069

Heavy-duty insert, Number of contacts: 12, Dimension: 1 module Spaces, Rated voltage : 250V, Rated current: 10A, Female insert, Crimping connector

Produktvorteile

- ☒ Crimping connection technology, applicable to a wide range of wire specifications ;
- ☒ Modular products, easy to assemble and maintain .

Zertifizierung von Produkten



Technische Daten

Produktzeichnung

3D-Modell

□

Marking

classification	Insert
Series	DM

versions

Connection method	Crimping connection
Female/Male	Female
Dimension	1 module
Number of positions	12
PE Contacts	No

Material characteristics

Material (insert)	Polycarbonate (PC)
Materia (Contact)	Copper alloy
Surface (Contact)	Silver plated/gold plated
Flammability rating	V-0
color	Grey/White (RAL 7032)
RoHS	Comply with RoHS exemptions

Electrical parameters

Rated current	10A
	250V
Rated pulse voltage	4KV
Pollution level	3
On the basis of UL /CSARated current	600V
Insulation resistance	≥10000MΩ
Contact resistance	≤3mΩ
Temperature range	-40℃~+125℃
working life-mating cycles	≥500 time
Conductor cross sections (mm²)	0.14-2.5mm²
Conductor cross sections(AWG)	26-14AWG

Standards

Connection meets standards	DIN EN 60664 DIN EN 61984
----------------------------	---------------------------

Zubehör

Accessories

Crimping tool Removal tool	/
----------------------------	---

Die Geschäftsdaten

Nummer der Bestellung	21020000069
Verpackung Einheit	
Minimale Bestellmenge	5
Produktgewicht (ohne Verpackung)	9