DEGSON

Aperçu

informations sur le produit

DG2350-50A(H)-12010000610

Single-layer PCB barrier terminal blocks,Rated current:120A.Rated voltage(UL):600V.Cross section:2-1/0AWG Pitch:23.5mm.Color:black,Contact surface:Tin

Les avantages des produits

☑ Screw connection for worldwide use
☑ Fence type wiring structure，stable and reliable connecion
☑ High current eletrical connections at power end can be met

Les certificates des produits

c UL® us

Caractéristiques techniques

Dessin de produit

Modèle 3D

Wiring capacity

torque	5.5N.m
Connectable conductor cross section	2~1/0AWG

Device properties

number of digits	23.5mm

Electrical parameters UL

Rated voltage (B)	600V
Rated voltage (C)	600V
Rated voltage (D)	600V

Rated current (B)	120A
Rated current (D)	5A
Rated current (C)	120A

Item properties

Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Connection method	Screw connection
Screwdriver	Phillips screwdriver
screw thread	M8
Number of potentials	4
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PBT
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059

Environmental data

Ambient temperature (operation)	-40℃~125℃

Accessoires

Caractéristiques commerciales

Numéro de la commande	12010000610
Unité d'emballage	20
Quantité minimale de commande	
Le poid de produit (sans emballage)	195.66