


## Aperçu

### informations sur le produit



## 8EDGKRMA-7.5-10020002775

Pluggable terminal blocks, Rated current: 20A. Rated voltage  
(III/2) : 400V, pitch: 7.5mm, Color: gray, Contact surface : Tin

### Les avantages des produits

- ☒ Adapt to multi-type plugs, device design is highly flexible
- ☒ Cage clamp connection technology, fast wiring
- ☒ Universal installation method, suitable for various situations

### Les certificats des produits



## Caractéristiques techniques

### Dessin de produit

### Modèle 3D

□

### Connection capacity

|                                  |                        |
|----------------------------------|------------------------|
| Conductor cross section solid    | 0.2~2.5mm <sup>2</sup> |
| Conductor cross section flexible | 0.2~2.5mm <sup>2</sup> |
| AWG                              | 22~14AWG               |
| Strip length                     | 9mm                    |

### Electrical parameters UL

|                   |      |
|-------------------|------|
| Rated voltage (B) | 300V |
| Rated voltage (D) | 300V |
| Rated current (B) | 15A  |
| Rated current (D) | 10A  |

Electrical parameters IEC

|                            |      |
|----------------------------|------|
| Rated voltage              | 400V |
| Rated current              | 20A  |
| Rated voltage(III/2)       | 400V |
| Rated surge voltage(III/2) | 4KV  |

Item properties

|                      |                               |
|----------------------|-------------------------------|
| Connection direction | 0°                            |
| Type of installation | panel                         |
| Pin arrangement      | Single row in a straight line |
| Connection method    | spring-cage connection        |
| Pitch                | 7.5mm                         |
| Number of potentials | 2                             |
| Pluggable or not     | Yes                           |
| Number of rows       | 1                             |

Material data

|                             |                           |
|-----------------------------|---------------------------|
| Environmental items         | Compliant with REACH/RoHS |
| Contact material            | copper                    |
| Contact point metal surface | tin-plated                |
| Contact zone metal surface  | tin-plated                |
| Insulation Materials        | PA66                      |
| Insulating material group   | I                         |
| Flammability rating         | UL94V-0                   |

Mechanical tests

|                    |                  |
|--------------------|------------------|
| Test Specification | IEC61984/ UL1059 |
|--------------------|------------------|

Environmental data

Ambient temperature (operation)

-40°C~105°C

## Accessoires

### Accessories

Coding strip

/

Bridge

DG018-7.5

Marking strip

/

Others

/

### Tool

Operating tool

DG010

Screwdriver

/

## Caractéristiques commerciales

Numéro de la commande

10020002775

Unité d'emballage

450

Quantité minimale de  
commande

30

Le poid de produit (sans  
emballage)

5