

Aperçu

informations sur le produit



DG260-10.0-10060001953

PCB spring terminal blocks, Rated current: 32A. Rated voltage
(III/2) : 630V, pitch: 10.0mm, Color: green, Contact surface : Tin

Les avantages des produits

- ☒ Universal installation method, suitable for various situations
- ☒ 45° connection can realize multi-row layout on PCB
- ☒ Different poles can be combined through the side lock

Les certificats des produits

Caractéristiques techniques

Dessin de produit

Modèle 3D

□

Processing notes

Process

Wave soldering/manual soldering

Connection capacity

Conductor cross section solid

0.2~4mm²

Conductor cross section flexible

0.2~4.0mm²

AWG

24~10AWG

Strip length

11mm

Electrical parameters UL

Rated voltage (B)

300V

Rated current (B)

30A

Electrical parameters IEC

Rated voltage	630V
Rated voltage(III/3)	630V
Rated current	32A
Rated voltage(III/2)	630V
Rated voltage(II/2)	1000V
Rated surge voltage(III/3)	6KV
Rated surge voltage(III/2)	6KV
Rated surge voltage(II/2)	6KV

Item properties

Connection direction	45°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Connection method	spring-cage connection
Pitch	10mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL1059
Environmental data	
Ambient temperature (operation)	-40°C~105°C

Accessoires	
Accessories	
Coding strip	/
Bridge	/
Marking strip	/
Others	/
Tool	
Operating tool	/
Screwdriver	/

Caractéristiques commerciales	
Numéro de la commande	10060001953
Unité d'emballage	50
Quantité minimale de commande	30
Le poid de produit (sans emballage)	10.235