


## Aperçu

### informations sur le produit



**5EDGKD-7.62-10020000918**

Pluggable terminal blocks, Rated current: 41A. Rated voltage  
(III/2) : 1000V, pitch: 7.62mm, Color: green, Contact surface : Tin

### Les avantages des produits

- ☒ Adapt to multi-type sockets, device design is highly flexible
- ☒ Keying parts can be installed
- ☒ Universal installation method, suitable for various situations

### Les certificats des produits



## Caractéristiques techniques

### Dessin de produit

### Modèle 3D

□

### Connection capacity

|                                  |           |
|----------------------------------|-----------|
| Conductor cross section solid    | 0.2~10mm² |
| Conductor cross section flexible | 0.2~10mm² |
| AWG                              | 24~8AWG   |
| Strip length                     | 14mm      |

### Electrical parameters UL

|                   |      |
|-------------------|------|
| Rated voltage (B) | 600V |
| Rated current (B) | 35A  |

### Electrical parameters IEC

|               |       |
|---------------|-------|
| Rated voltage | 1000V |
|---------------|-------|

|                            |       |
|----------------------------|-------|
| Rated voltage(III/3)       | 1000V |
| Rated current              | 41A   |
| Rated voltage(III/2)       | 1000V |
| Rated voltage(II/2)        | 1000V |
| Rated surge voltage(III/3) | 8KV   |
| Rated surge voltage(III/2) | 8KV   |
| Rated surge voltage(II/2)  | 6KV   |

#### Item properties

|                      |        |
|----------------------|--------|
| Connection direction | 0°     |
| Pitch                | 7.62mm |
| Number of potentials | 2      |
| Pluggable or not     | Yes    |
| Number of rows       | 1      |

#### Material data

|                             |                           |
|-----------------------------|---------------------------|
| Environmental items         | Compliant with REACH/RoHS |
| Contact material            | copper                    |
| Contact point metal surface | tin-plated                |
| Insulation Materials        | PA66                      |
| Insulating material group   | I                         |
| Flammability rating         | UL94V-0                   |

#### Mechanical tests

|                    |                  |
|--------------------|------------------|
| Test Specification | IEC61984/ UL1059 |
|--------------------|------------------|

#### Environmental data

|                                 |           |
|---------------------------------|-----------|
| Ambient temperature (operation) | -40℃~105℃ |
|---------------------------------|-----------|

## Accessoires

### Tool

Screwdriver

/

Operating tool

/

### Accessories

Coding strip

5EDG-PWI

Bridge

/

Marking strip

/

Others

/

## Caractéristiques commerciales

Numéro de la commande

10020000918

Unité d'emballage

375

Quantité minimale de commande

30

Le poids de produit (sans emballage)

10.27