

Aperçu

Informations sur le produit



DG243-7.5-10060002350

PCB spring terminal blocks, Rated current: 17A. Rated voltage
(III/2) : 750V, pitch: 7.5mm, Color: gray, Contact surface : Tin

Les avantages des produits

- ☒ Cage clamp connection technology, fast wiring
- ☒ Different poles can be combined through the side lock
- ☒ Universal installation method to ensure a high degree of flexibility in device design

Les certificats des produits



Caractéristiques techniques

Dessin de produit

Modèle 3D

□

Processing notes

Process

Wave soldering/manual soldering

Connection capacity

Conductor cross section solid

0.2~2.5mm²

Conductor cross section flexible

0.2~2.5mm²

AWG

28~12AWG

Strip length

6mm

Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (D)

300V

Rated current (B)	15A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	750V
Rated current	17A
Rated voltage(III/2)	750V
Rated power frequency voltage(1min)	3KV

Item properties

Connection direction	45°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Connection method	spring-cage connection
Pitch	7.5mm
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

Accessoires

Accessories

Coding strip	/
--------------	---

Bridge	/
--------	---

Marking strip	/
---------------	---

Others	/
--------	---

Tool

Operating tool	/
----------------	---

Screwdriver	/
-------------	---

Caractéristiques commerciales

Numéro de la commande	10060002350
-----------------------	-------------

Unité d'emballage	875
-------------------	-----

Quantité minimale de commande	30
-------------------------------	----

Le poids de produit (sans emballage)	1.42
--------------------------------------	------