

Aperçu

Informations sur le produit



2EDGVC-5.0-10030002301

Pluggable terminal blocks, Rated current: 20A. Rated voltage (III/2) : 320V, pitch: 5.0mm, Color: green, Contact surface : Tin

Les avantages des produits

- ☒ Universal installation method to ensure a high degree of flexibility in device design
- ☒ The plug direction is perpendicular to PCB

Les certificats des produits



Caractéristiques techniques

Dessin de produit

Modèle 3D

□

Processing notes

Process

Wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	15A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	320V
Rated current	20A

Rated voltage(III/2)	320V
Rated surge voltage(III/2)	4KV

Item properties

Connection direction	90°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Pitch	5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

Accessoires

Tool

Screwdriver	/
-------------	---

Operating tool	/
Accessories	
Coding strip	/
Bridge	/
Marking strip	/
Others	2EDG-PWP-01H

Caractéristiques commerciales	
Numéro de la commande	10030002301
Unité d'emballage	200
Quantité minimale de commande	30
Le poid de produit (sans emballage)	0.97