


Aperçu

Informations sur le produit



8EDGVC-3.5-10030002857

Pluggable terminal blocks, Rated current: 10A. Rated voltage
(III/3) : 130V, pitch: 3.5mm, Color: gray, Contact surface : Tin

Les avantages des produits

- ☒ Universal installation method to ensure a high degree of flexibility in device design
- ☒ The plug direction is perpendicular to PCB

Les certificats des produits



Caractéristiques techniques

Dessin de produit

Modèle 3D

□

Processing notes

Process

Wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	10A
Rated current (D)	10A

Electrical parameters IEC

Rated voltage	130V
Rated voltage(III/3)	130V

Rated current	10A
Rated surge voltage(III/3)	2.5KV

Item properties

Connection direction	90°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Pitch	3.5mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

Accessoires

Tool

Screwdriver	/
Operating tool	/

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	/

Caractéristiques commerciales	
Numéro de la commande	10030002857
Unité d'emballage	500
Quantité minimale de commande	30
Le poid de produit (sans emballage)	0.48