

Aperçu

Informations sur le produit



DG211R-2.5-10060001760

PCB spring terminal blocks, Rated current: 3A. Rated voltage
(III/2) : 160V, pitch: 2.5mm, Color: gray, Contact surface : Tin

Les avantages des produits

- ☒ PUSH-IN connection technology, fast wiring
- ☒ Different poles can be combined through the side lock
- ☒ Universal installation method to ensure a high degree of flexibility in device design

Les certificats des produits



Caractéristiques techniques

Dessin de produit

Modèle 3D

□

Processing notes

Process

Wave soldering/manual soldering

Connection capacity

Conductor cross section solid

0.2~0.5mm²

Conductor cross section flexible

0.2~0.5mm²

AWG

28~20AWG

Strip length

9mm

Electrical parameters UL

Rated voltage (B)

150V

Rated current (B)

5A

Electrical parameters IEC

Rated voltage	160V
Rated voltage(III/3)	160V
Rated current	3A
Rated voltage(III/2)	160V
Rated voltage(II/2)	320V
Rated surge voltage(III/3)	2.5KV
Rated surge voltage(III/2)	2.5KV
Rated surge voltage(II/2)	2.5KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Connection method	Push-in spring connection
Pitch	2.5mm
Number of potentials	2
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I

Flammability rating	UL94V-0
Mechanical tests	
Test Specification	IEC60947/UL1059
Environmental data	
Ambient temperature (operation)	-40°C~105°C

Accessoires	
Accessories	
Coding strip	/
Bridge	/
Marking strip	/
Others	/
Tool	
Operating tool	/
Screwdriver	/

Caractéristiques commerciales	
Numéro de la commande	10060001760
Unité d'emballage	2400
Quantité minimale de commande	30
Le poid de produit (sans emballage)	1.28