

총람

제품 장점



DG15HS-1.2-10080000058

Feed through terminal blocks, Rated current: 76A. Rated voltage
(III/2) : 750V, pitch: 15.0mm, Color: natural, Contact surface : Zn

제품 장점

- ☒ Can realize horizontal wire-to-wire connection
- ☒ Panel mounting, suitable for various situations

제품 인증



기술 데이터

제품 도면

3D

□

Connection capacity

Conductor cross section solid	2.5~16mm ²
Conductor cross section flexible	2.5~16mm ²
AWG	12~10AWG
Torque	1.2N.m
Strip length	10mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (D)	300V
Rated current (B)	30A

Rated current (D)	10A
-------------------	-----

Electrical parameters IEC

Rated current	
	76A
Rated voltage(III/2)	750V
Rated power frequency voltage(1min)	3KV

Item properties

Type of installation	panel
Connection method	Screw connection
Screwdriver	Slotted screwdriver
screw thread	M4
Pitch	15mm
Number of potentials	12
Pluggable or not	no

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	steel
Contact point metal surface	Galvanized
Insulation Materials	PA66
Flammability rating	UL94V-2

Mechanical tests

Test Specification	UL1059/IEC60998
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

Accessories	
Coding strip	/
Bridge	/
Marking strip	/
Others	/
Tool	
Operating tool	/
Screwdriver	/

비즈니스 데이터	
발주 번호	10080000058
포장 단위	40
MOQ	30
제품 무게 (포장 제외)	93.8