


## Überblick

### Informationen zum Produkt



**5EDGKHM-7.62-10010004409**

Pluggable terminal blocks, Rated current: 41A. Rated voltage  
(III/2) : 1000V, pitch: 7.62mm, Color: green, Contact surface : Tin

### Produktvorteile

- ☒ Adapt to multi-type sockets, device design is highly flexible
- ☒ Keying parts can be installed
- ☒ Universal installation method, suitable for various situations

### Zertifizierung von Produkten



## Technische Daten

### Produktzeichnung

### 3D-Modell

□

### Connection capacity

|                                  |                        |
|----------------------------------|------------------------|
| Conductor cross section solid    | 0.5~6mm <sup>2</sup>   |
| Conductor cross section flexible | 0.5~6.0mm <sup>2</sup> |
| Torque                           | 0.8N.m                 |
| Strip length                     | 11mm                   |

### Electrical parameters UL

|                   |      |
|-------------------|------|
| Rated voltage (B) | 600V |
| Rated voltage (C) | 600V |
| Rated voltage (D) | 600V |
| Rated current (B) | 41A  |

|                   |     |
|-------------------|-----|
| Rated current (D) | 5A  |
| Rated current (C) | 41A |

#### Electrical parameters IEC

|                            |       |
|----------------------------|-------|
| Rated voltage              | 1000V |
| Rated voltage(III/3)       | 1000V |
| Rated current              | 41A   |
| Rated voltage(III/2)       | 1000V |
| Rated voltage(II/2)        | 1000V |
| Rated surge voltage(III/3) | 8KV   |
| Rated surge voltage(III/2) | 8KV   |
| Rated surge voltage(II/2)  | 6KV   |

#### Item properties

|                      |                              |
|----------------------|------------------------------|
| Connection direction | 0°                           |
| Screwdriver          | slotted-phillips screwdriver |
| screw thread         | M3                           |
| Pitch                | 7.62mm                       |
| Number of potentials | 2                            |
| Pluggable or not     | Yes                          |
| Number of rows       | 1                            |

#### Material data

|                             |                           |
|-----------------------------|---------------------------|
| Environmental items         | Compliant with REACH/RoHS |
| Contact material            | copper                    |
| Contact point metal surface | tin-plated                |
| Insulation Materials        | PA66                      |
| Insulating material group   | I                         |

|                                 |                  |
|---------------------------------|------------------|
| Flammability rating             | UL94V-0          |
| Mechanical tests                |                  |
| Test Specification              | IEC61984/ UL1059 |
| Environmental data              |                  |
| Ambient temperature (operation) | -40°C~105°C      |

|                |   |
|----------------|---|
| Zubehör        |   |
| Tool           |   |
| Screwdriver    | / |
| Operating tool | / |
| Accessories    |   |
| Coding strip   | / |
| Bridge         | / |
| Marking strip  | / |
| Others         | / |

|                                  |             |
|----------------------------------|-------------|
| Die Geschäftsdaten               |             |
| Nummer der Bestellung            | 10010004409 |
| Verpackung Einheit               | 160         |
| Minimale Bestellmenge            |             |
| Produktgewicht (ohne Verpackung) | 10.94       |