


Überblick

Informationen zum Produkt



8EDGKG-7.62-10020001351

Pluggable terminal blocks, Rated current: 20A. Rated voltage
(III/3) : 400V, pitch: 7.62mm, Color: gray, Contact surface : Tin

Produktvorteile

- ☒ Adapt to multi-type sockets, device design is highly flexible
- ☒ Cage clamp connection technology, fast wiring
- ☒ Universal installation method, suitable for various situations

Zertifizierung von Produkten



Technische Daten

Produktzeichnung

3D-Modell

Connection capacity

Conductor cross section solid	0.2~2.5mm ²
Conductor cross section flexible	0.2~2.5mm ²
AWG	22~14AWG
Strip length	10mm

Electrical parameters UL

Rated voltage (B)	300V
Rated voltage (C)	300V
Rated current (B)	15A
Rated current (C)	15A

Electrical parameters IEC

Rated voltage	400V
Rated voltage(III/3)	400V
Rated current	20A
Rated surge voltage(III/3)	4KV

Item properties

Connection direction	0°
Connection method	spring-cage connection
Pitch	7.62mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40℃~105℃
---------------------------------	-----------

Zubehör

Tool

Screwdriver

/

Operating tool

DG010

Accessories

Coding strip

/

Bridge

DG018-7.5

Marking strip

/

Others

DG017

Die Geschäftsdaten

Nummer der Bestellung

10020001351

Verpackung Einheit

100

Minimale Bestellmenge

Produktgewicht (ohne
Verpackung)

4.3