

Überblick

Informationen zum Produkt



15EDGRH-2.5-10030000330

Pluggable terminal blocks, Rated current: 5A. Rated voltage
(II / 2) : 250V, pitch: 2.5mm, Color: green, Contact surface : Tin

Produktvorteile

- ☒ Universal installation method to ensure a high degree of flexibility in device design
- ☒ Multi-layer wire connection can achieve higher contact density

Zertifizierung von Produkten



Technische Daten

Produktzeichnung

3D-Modell

□

Processing notes

Process

Wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)

150V

Rated current (B)

5A

Electrical parameters IEC

Rated voltage

100V

Rated current

4A

Rated voltage(II/2)

100V

Rated surge voltage(II/2)

2.5KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Pitch	2.5mm
Number of potentials	4
Pluggable or not	Yes
Number of rows	2

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC61984/ UL1059
--------------------	------------------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

Zubehör

Tool

Screwdriver	/
Operating tool	/

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	15EDG-PWI-2.5

Die Geschäftsdaten

Nummer der Bestellung	10030000330
Verpackung Einheit	100
Minimale Bestellmenge	
Produktgewicht (ohne Verpackung)	1.66