

概要

製品情報



DPD4/1.5-06P-11040001590

Direct insertion connection, rated voltage: 450V, rated current: 17.5A, connection quantity: 7, wiring capacity: 0.14-1.5mm² (load), 0.5mm² -4mm² (main circuit), AWG: 26-14 (load), 20AWG~10AWG (main circuit), width: 25.8mm, color: gray, installation method: NS35/15 rail installation, flat installation

製品の特長

☑ Flexible splicing and bridging design ☑ Unique heat dissipation structure ☑ Universal installation method, suitable for various occasions ☑ Snap on identification structure, quick and stable installation

製品認証



技術データ

製品チャート

3Dモデル

□

Wiring data

Strip length

10~12mm

Environmental conditions

Ambient temperature (operation)

-40 °C ~ 105 °C (depending on derating curve)

Relative humidity (storage/transport)

25%~75%

Electrical parameters IEC

Rated voltage(III/3)

450V

IEC Electrical parameters

Rated surge voltage	6KV
---------------------	-----

Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Overview

Number of rows	1
number of connections	7
Open-end side panels	no
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

アクセサリ

Attachment

Same direction installation rail adapter	DPD-NS35A
Vertical installation rail adapter	DPD-NS15/35
Panel installation adapter	DPD1.5-F
Identification cards	ZSF3.5
Bridge components	DFBSXX-3.5

ビジネスデータ

注文番号	11040001590
パッキングユニット	
最小注文数量	
1 個あたりの重量（梱包を含めない）	

