DEGSON

概要

製品情報

DPD1.5-12P-11040001488

Direct insertion connection, rated voltage: 450V, rated current: 17.5A, connection quantity: 12, wiring capacity: 0.14-1.5mm², AWG: 26-14, width: 25.8mm, color: gray, installation method: NS35/15 rail installation, flat installation rail installation, flat installation

製品の特長

☑ Flexible splicing and bridging design ☑ Unique heat dissipation structure ☑ Universal installation method, suitable for various occasions ☑ Snap on identification structure, quick and stable installation

製品認証

技術データ

製品チャート

3Dモデル

Wiring data

Strip length	10~12mm
Conductor cross section solid AWG	26~14

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C（depending on derating curve）
Relative humidity (storage/transport)	25%~75%

Electrical parameters IEC

Rated voltage(III/3)	450V

IEC Electrical parameters

Rated current (III / 3)	17.5A
Rated surge voltage	6KV

Environmental protection

REACh SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Overview

Number of rows	1
Open-end side panels	no
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

アクセサリ

Attachment

Same direction installation rail adapter	DPD-NS35A
Vertical installation rail adapter	DPD-NS15/35
Panel installation adapter	DPD1.5-F
Identification cards	ZSF3.5
Bridge components	DFBSXX-3.5

ビジネスデータ

注文番号	11040001488
パッキングユニット	
最小注文数量	
１個あたりの重量（梱包を含めない）	