


概要

製品情報



DPD2.5-02P-11-00(Z)-11040001316

Direct insertion connection, rated voltage: 690V, rated current: 24A, connection quantity: 2, wiring capacity: 0.14~2.5mm², AWG: 26~12, width: 28.6mm, color: gray, installation method: NS35/15

製品の特長

☒ Flexible splicing and bridging design
 ☒ Unique heat dissipation structure
 ☒ Universal installation method, suitable for various occasions
 ☒ Snap on identification structure, quick and stable installation

製品認証



技術データ

製品チャート

3Dモデル

□

Wiring data

Strip length	10~12mm
Conductor cross section solid AWG	26~12

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
Relative humidity (storage/transport)	25%~75%

IEC Electrical parameters

Rated current (III / 3)	24A
Rated surge voltage	8KV

Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Electrical performance test

Temperature rise test result	Passed the test
------------------------------	-----------------

Dimension

NS 35/7,5 Height	32.1mm
	39.7mm

Overview

Connection type	In line connection
Number of rows	1
number of connections	2
Open-end side panels	no
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

アクセサリ

Accessories

Same direction installation rail adapter	DPD-NS35A
Vertical installation rail adapter	DPD-NS15/35
Panel installation adapter	DPD-F
Identification cards	ZSF5
Bridge components	DFBSXX-5.2

ビジネスデータ

注文番号	11040001316
パッキングユニット	
最小注文数量	
1 個あたりの重量（梱包を 含めない）	