


概要

製品情報



DPD4-06P-11150000001

Direct insertion connection, rated voltage: 450V, rated current: 32A, connection quantity: 6, wiring capacity: 0.2~4mm², AWG: 24~12, width: 30.5mm, color: gray, installation method: NS35/15 rail installation, flat installation rail installation, flat installation

製品の特長

☑ Flexible splicing and bridging design ☑ Unique heat dissipation structure ☑ Universal installation method, suitable for various occasions ☑ Snap on identification structure, quick and stable installation

製品認証



技術データ

製品チャート

3Dモデル

□

Wiring data

Conductor cross section flexible (ferrule with plastic sleeve)	0.2~4mm ²
Strip length	10~12mm
Conductor cross section solid	0.2~6mm ²
Conductor cross section solid AWG	26~10

Environmental conditions

Ambient temperature (operation)	-40 °C ~ 105 °C (depending on derating curve)
---------------------------------	---

Electrical parameters IEC

Rated voltage(III/3)	450V
----------------------	------

IEC Electrical parameters

Rated current (III / 3)	32A
Rated surge voltage	6KV

Environmental protection

REACH SVHC	Lead 7439-92-1
RoHS	No excessive harmful substances

Material data

Flammability rating	UL94V-2
---------------------	---------

Dimension

Height	30.5mm
--------	--------

Overview

Number of rows	1
number of connections	6
Open-end side panels	no
Insulation Materials	PA
Flame retardant grade, in line with UL 94	V0

アクセサリ

Attachment

Same direction installation rail adapter	DPD4-NS35A
Vertical installation rail adapter	DPD-NS15/35
Panel installation adapter	DPD4-F
Identification cards	ZSF6
Bridge components	DFBSXX-6.2

ビジネスデータ

注文番号	11150000001
パッキングユニット	
最小注文数量	
1 個あたりの重量（梱包を 含めない）	