

총람

제품 장점



DG2002-4.0-300A(H)-10060001736

PCB spring terminal blocks, Rated current: 9A. Rated voltage (III/2) : 160V, pitch: 4.0mm, Color: White, Contact surface : Tin

제품 장점

- ☒ PUSH-IN connection technology, fast wiring
- ☒ Suitable for SMT welding process
- ☒ Compact structure, saving installation space

제품 인증



기술 데이터

제품 도면

3D

□

Electrical parameters UL

Rated current (B)

9A

Electrical parameters IEC

Rated voltage

160V

Rated voltage(III/3)

32V

Rated current

9A

Rated voltage(III/2)

160V

Rated voltage(II/2)

160V

Rated surge voltage(III/3)

4KV

Rated surge voltage(III/2)

4KV

Rated surge voltage(II/2)	4KV
---------------------------	-----

Item properties

Connection direction	0°
Pitch	4mm
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Insulation Materials	High temperature resistant materials
Insulating material group	IIIa
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL1977
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40℃~130℃
---------------------------------	-----------

악세사리

Accessories

Coding strip	/
Bridge	DG027-4.0
Marking strip	/
Others	/

Tool

Operating tool	DG028
----------------	-------

Screwdriver

/

비즈니스 데이터

발주 번호	10060001736
포장 단위	0
MOQ	30
제품 무게 (포장 제외)	0.64