

총람

제품 장점



DG263-10.0-10060002758

PCB spring terminal blocks, Rated current: 41A. Rated voltage
(III/2) : 1000V, pitch: 10.0mm, Color: gray, Contact surface : Tin

제품 장점

- ☒ Universal installation method, suitable for various situations
- ☒ 45° connection can realize multi-row layout on PCB
- ☒ Different poles can be combined through the side lock

제품 인증



기술 데이터

제품 도면

3D

□

Processing notes

Process

Wave soldering/manual soldering

Connection capacity

Conductor cross section solid

0.2~6mm²

Conductor cross section flexible

0.2~6.0mm²

AWG

24~10AWG

Strip length

12mm

Electrical parameters UL

Rated voltage (B)

300V

Rated current (B)

30A

Electrical parameters IEC

Rated voltage	1000V
Rated voltage(III/3)	630V
Rated current	41A
Rated voltage(III/2)	1000V
Rated voltage(II/2)	1000V
Rated surge voltage(III/3)	8KV
Rated surge voltage(III/2)	8KV
Rated surge voltage(II/2)	8KV

Item properties

Connection direction	45°
Type of installation	PCB welding
Pin arrangement	Double-row in a straight line
Connection method	spring-cage connection
Pitch	10mm
Number of potentials	1
Pluggable or not	no
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	copper
Contact point metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I

Flammability rating	UL94V-0
Mechanical tests	
Test Specification	IEC60947/UL1059
Environmental data	
Ambient temperature (operation)	-40℃~105℃

악세서리	
Accessories	
Coding strip	/
Bridge	/
Marking strip	/
Others	/
Tool	
Operating tool	/
Screwdriver	/

비즈니스 데이터	
발주 번호	10060002758
포장 단위	100
MOQ	30
제품 무게 (포장 제외)	5.894