

## 총람

### 제품 장점



### 8EDGA-5.0-10020000980

Pluggable terminal blocks, Rated current: 20A. Rated voltage (III/3) : 320V, pitch: 5.0mm, Color: gray, Contact surface : Tin

### 제품 장점

- ☒ PCB welding, plug direction is parallel to the PCB
- ☒ Provides anti-touch protection for connection

### 제품 인증



## 기술 데이터

### 제품 도면

#### 3D

□

### Connection capacity

Strip length

6mm

### Electrical parameters UL

Rated voltage (B)

300V

Rated voltage (D)

300V

Rated current (B)

15A

Rated current (D)

10A

### Electrical parameters IEC

Rated voltage

320V

Rated voltage(III/3)

320V

|                            |     |
|----------------------------|-----|
| Rated current              | 20A |
| Rated surge voltage(III/3) | 4KV |

Item properties

|                      |                        |
|----------------------|------------------------|
| Connection direction | 0°                     |
| Connection method    | spring-cage connection |
| Pitch                | 5mm                    |
| Number of potentials | 2                      |
| Pluggable or not     | Yes                    |
| Number of rows       | 1                      |

Material data

|                             |                           |
|-----------------------------|---------------------------|
| Environmental items         | Compliant with REACH/RoHS |
| Contact material            | copper                    |
| Contact point metal surface | tin-plated                |
| Contact zone metal surface  | tin-plated                |
| Insulation Materials        | PA66                      |
| Insulating material group   | I                         |
| Flammability rating         | UL94V-0                   |

Mechanical tests

|                    |                  |
|--------------------|------------------|
| Test Specification | IEC61984/ UL1059 |
|--------------------|------------------|

Environmental data

|                                 |           |
|---------------------------------|-----------|
| Ambient temperature (operation) | -40℃~105℃ |
|---------------------------------|-----------|

악세사리

Tool

|             |   |
|-------------|---|
| Screwdriver | / |
|-------------|---|

|                |   |
|----------------|---|
| Operating tool | / |
| Accessories    |   |
| Coding strip   | / |
| Bridge         | / |
| Marking strip  | / |
| Others         | / |

|               |             |
|---------------|-------------|
| 비즈니스 데이터      |             |
| 발주 번호         | 10020000980 |
| 포장 단위         | 910         |
| MOQ           | 30          |
| 제품 무게 (포장 제외) | 1.97        |