

## Áttekintés

## Termék információ

**TSCB4-10070000056**

Transformer terminal blocks, Rated current: 32A. Rated voltage  
(III/2) : 800V, Color: Orange, Contact surface : Tin

## A termék előnyei

- ☒ Screw connection technology, safe and reliable
- ☒ Rail installation method, suitable for transformer wiring

## Termék tanúsítás



## Műszaki adatok

## Termékrajz

## 3D modell

□

## Connection capacity

|                                  |                       |
|----------------------------------|-----------------------|
| Conductor cross section solid    | 0.2~10mm <sup>2</sup> |
| Conductor cross section flexible | 0.2~10mm <sup>2</sup> |
| AWG                              | 24~6AWG               |
| Torque                           | 0.5N.m                |
| Strip length                     | 11mm                  |

## Electrical parameters UL

|                   |      |
|-------------------|------|
| Rated voltage (B) | 600V |
| Rated voltage (C) | 600V |
| Rated voltage (D) | 600V |

|                   |     |
|-------------------|-----|
| Rated current (B) | 30A |
| Rated current (D) | 5A  |
| Rated current (C) | 30A |

Electrical parameters IEC

|                            |       |
|----------------------------|-------|
| Rated current              |       |
|                            | 32A   |
| Rated voltage(III/2)       | 800V  |
| Rated surge voltage(III/2) | 2.5KV |

Item properties

|                      |                     |
|----------------------|---------------------|
| Type of installation | panel               |
| Connection method    | Screw connection    |
| Screwdriver          | Slotted screwdriver |
| screw thread         | M4                  |
| Number of potentials | 1                   |
| Pluggable or not     | no                  |
| Number of rows       | 1                   |

Material data

|                             |                           |
|-----------------------------|---------------------------|
| Environmental items         | Compliant with REACH/RoHS |
| Contact material            | copper                    |
| Contact point metal surface | tin-plated                |
| Insulation Materials        | PA66                      |
| Insulating material group   | I                         |
| Flammability rating         | UL94V-0                   |

Mechanical tests

|                    |                 |
|--------------------|-----------------|
| Test Specification | UL1059/IEC60998 |
|--------------------|-----------------|

Environmental data

Ambient temperature (operation)

-40°C~105°C

Melléklet

Accessories

|               |      |
|---------------|------|
| Coding strip  | TZB4 |
| Bridge        | /    |
| Marking strip | /    |
| Others        | /    |

Tool

|                |   |
|----------------|---|
| Operating tool | / |
| Screwdriver    | / |

Üzleti adatok

|                                      |             |
|--------------------------------------|-------------|
| Rendelészám                          | 10070000056 |
| Csomagolási egység                   | 100         |
| Minimális rendelési mennyiség        | 30          |
| A termékek súlya (csomagolás nélkül) | 3.75        |