


Áttekintés

Termék információ

**15EDGRC-5.08-10030000281**

Pluggable Terminal Blocks
nominal current 7A, Rated voltage (II/2):
450V, pitch: 5.08mm, Color: green, Contact surface: Tin

A termék előnyei

- ☒ Universal installation method to ensure a high degree of flexibility in device design
- ☒ The plug direction is parallel to the PCB

Termék tanúsítás



Műszaki adatok

Termékrajz

3D modell



Processing notes

Process

Wave soldering/manual soldering

Electrical parameters UL

Rated voltage (B)

300V

Rated current (B)

8A

Electrical parameters IEC

Rated voltage

450V

Rated current

7A

Rated voltage(II/2)

450V

Rated surge voltage(II/2)

4KV

Item properties

Connection direction	0°
Type of installation	PCB welding
Pin arrangement	Single row in a straight line
Pitch	5.08mm
Number of potentials	2
Pluggable or not	Yes
Number of rows	1

Material data

Environmental items	Compliant with REACH/RoHS
Contact material	Copper alloy
Contact zone metal surface	tin-plated
Insulation Materials	PA66
Insulating material group	I
Flammability rating	UL94V-0

Mechanical tests

Test Specification	IEC60947/UL1059
--------------------	-----------------

Environmental data

Ambient temperature (operation)	-40°C~105°C
---------------------------------	-------------

Melléklet

Tool

Screwdriver	/
Operating tool	/

Accessories

Coding strip	/
Bridge	/
Marking strip	/
Others	15EDG-PWI

Üzleti adatok

Rendelészám	10030000281
Csomagolási egység	
Minimális rendelési mennyiség	
A termékek súlya (csomagolás nélkül)	